

## LMC-02.GF Gigabit Ethernet Media Converter Ruggedized type

### Description:

The LMC series introduces the media converter housed in a robust metal box. It provides Expanded Beam connectors for fiber optic cable and copper twisted pairs ports for harsh environmental conditions. The LMC rugged design extends the use of Ethernet in harsh environmental conditions - heavy industry, petrochemical, mines, broadcasting and other field applications. It meets the demands for mobility, easy installation and the mechanical resistance necessary for deployment in the field. The LMC converters give you the freedom to extend your 10/100/1000 Mbps cabling distance by allowing connectivity up to 2 km over MM fiber, up to 50 kilometers if use the SM fiber. LED indicators show the power status of the converter, LAN port and fiber activity.

The basic LMC-02.GF configuration includes two independent media converters in one box. The optical and electrical ports of both converters are terminated at separate connectors, HMA type for FO, rugged RJ-45 for copper LAN interface. Power supply for both converters is ensured via one connector.



### Features:

- Two 1G media converters
- 10/100/1000BASE-T to 100/1000BASE-X converter
- Auto-Cross over for MDI/MDIX in TP port
- Auto-Negotiation or Manual mode in TP port
- Support flow control Enable or Disable
- Support Jumbo Frame 9K Packet
- Ingress/Egress Bandwidth control
- Support 802.3ah-OAM/IP in-band management
- Firmware upgrade via Web
- Management Password Setting
- Dying gasp (remote power failure detection)
- Support Link Fault Pass Through (LFP) Function
- Support Auto Laser Shutdown (ALS) Function
- Web management on stand-alone.
- Support On-Line F/W upgrade (local) by the Web manager
- Support 16 Tag VLAN Group
- RMON counters

## Specifications:

For more detailed information contact our sales department **[SALES@OPTOKON.COM](mailto:SALES@OPTOKON.COM)**